

Roller Blind




C30 EASY ROLL



Chain-operated roller blind system. Direct clutch

Small and medium-sized roller blinds provide a simple and functional solution for managing natural light and enhancing indoor comfort. Suitable for residential, commercial and professional environments, they combine a clean, practical design with reliable performance. The chain-operated mechanism allows smooth and precise adjustment of the blind during raising and lowering. Their compact dimensions make them particularly suitable for installations where space is limited and the overall size of the roller system must be kept to a minimum. Available with dim-out, blackout and screen fabrics, they provide effective solar protection, enhanced privacy and improved energy efficiency. They can be wall- or ceiling-mounted using fixing brackets designed for quick and secure installation.

Exploded View and dimensions



Roll types

Standard



Optional



Roll type B recommended to cover window handle clearance

Children's security system

Standard


Art. 3238



Art. 3238 - Child safety system with transparent safety cord tensioner
 Child safety systems. Everyday objects in the home can represent a potential hazard for children, especially blind cords and chains.
 To prevent children from becoming entangled in blind cords or chains, with the risk of strangulation, it is recommended to keep beds and cots away from windows fitted with blinds. Rilox Italia offers a range of products designed for safe use in compliance with the UNI EN 13120:2014 standard.
 Roller blinds: chain-operated systems supplied with the safety chain tensioner Art. 3238, designed to prevent the chain from hanging loose and to keep it out of children's reach.

Chain control

Standard



Art. 3200R - Continuous chain loop, pitch 6x4,5

- 1 Bianco
White
- 2 Nero
Black
- 6 Grigio
Grey

Direct clutch

Standard

Hole to facilitate the chain's insertion



Spring

Steel core

Central body

Clutch cover

Screw

Crown cover

Crown gear


Chain guide

Technical features:

- High-performance harmonic steel wire spring, designed to provide stable and long-lasting locking performance.
- Heat-treated steel core, ensuring increased durability and wear resistance.
- Central body made of high-quality technical polymers, offering excellent resistance to abrasion and deterioration.
- Clutch cover: the structure is reinforced by the fins integrated into tube 8653.
- Crown with gear for 6x4.5 mm pitch chains, ensuring efficient and direct operation.
- Chain guide with bell-shaped paddle, allowing blind operation even from an off-centre position.
- Crown cover with opening for chain insertion.
- Maximum load capacity: 3 kg.
- Available colours: white, black and grey.

End cap with steel pin

Standard



Technical Features:

- Wheel designed to allow quick attachment and release from the bracket.
- Chrome-plated steel pin, ensuring strength and silent operation.
- Pin holder shaft equipped with a spring, allowing fast and secure installation.
- End cap with fins, designed for precise and easy coupling with the 30 mm tube 8653.
- Available colours: white, black and grey

Supports

Standard



Technical features:

- High-quality steel plates
- Ceiling or wall fixing
- Suitable for 30 mm blinds
- High-quality technopolymer carter
- Simple and refined design
- Available colours: white, black and grey

Reinforced Ø30mm tube Art.8653


Standard

Art. 8653 Patent pending

Technical features:


Extruded aluminium alloy roller tube:

- 6060 T6 extruded aluminium alloy tube compliant with UNI EN 755-9





Fixing

Ceiling




Wall



Bottom bar

Standard

Art. 8613



Art. 8613 – 30 × 8 mm extruded 6060 T6 aluminium alloy profile, compliant with UNI EN 755-9, powder-coated with QUALICOAT-certified polyester resin coating:


White – RAL 9010

Black – RAL 9005

Grey – matt oxidised-effect finish


Optional

Art. 8455



Optional

Art. 2755



Art. 8455 – Ø 22 mm extruded 6060 T6 aluminium alloy tube, compliant with UNI EN 755-9:

White – RAL 9010

Black – RAL 9005

Grey – anodised

Art. 2755 – Bottom bar made of extruded 6060 T6 aluminium alloy, compliant with UNI EN 755-9:

White – RAL 9010

Side decorative caps

Optional

Art. 8658 SHORT mm. 55



- 1 Bianco  White
- 2 Nero  Black
- 6 Grigio  Grey

Optional

Art. 8657 TALL mm. 65



- 1 Bianco  White
- 2 Nero  Black
- 6 Grigio  Grey



Rilox Italia Srl - Cap. Soc. € 150.000,00 I.V.
 Via Cascina Borniola, 15/A - 10036 Settimo Torinese (TO) - ITALY
 Reg. Imprese Torino - C.F. - P. IVA - 10634150014 - R.E.A. 1149982
 Ufficio Registro TORINO 2 - PEC: riloxitalia@pec.it
 Tel: (+39) 011 262 5473 - Fax: (+39) 011 22 22 250

www.riloxitalia.it



@rilox.italia



#riloxitalia